SRS ViVA 1 topsynth plus FE



High Performance Low Friction Engine Oil

August 2019

Characteristics

SRS ViVA 1 topsynth plus FE is a high performance low friction engine oil of viscosity grade SAE 5W-30. Base oils using synthetic technology and innovative additives matched to them ensure that the demands of today's practice are met. Excellent cold starting ensures optimal security of lubrication in the cold running phase. Extreme loads and high temperatures are safely handled under all operating conditions. SRS ViVA 1 topsynth plus FE contributes to the protection of the environment through its high fuel saving and the consequent reduction in emissions.

Application

SRS ViVA 1 topsynth plus FE is a top quality for passenger car gasoline and diesel engines of the new generation. The highest demands currently made on automobile engine oils are satisfied with more than enough reserve even after extended oil change intervals.

Specifications

- SAE Grade 5W-30
- ACEA A3/B4
- API SN

Approvals

- MB-Approval 229.5
- VW-Norm 502 00 and 505 00

Recommendations

• Renault RN 0700 / 0710

SRS ViVA 1 topsynth plus FE is a product of the H&R ChemPharm GmbH.

Typical data		Test method	SRS ViVA 1 topsynth plus FE
SAE Grade		SAE J 300	5W-30
Density at 15°C	g/cm³	DIN 51 757	0.856
Dyn. Viscosity at -30°C	mPa s	ASTM D 5293	5,120
Kin. Viscosity at 40°C	mm²/s	DIN EN ISO 3104	71.9
Kin. Viscosity at 100°C	mm²/s	DIN EN ISO 3104	12.1
Viscosity Index (VI)		DIN ISO 2909	167
Flash point COC	°C	DIN ISO 2592	230
Pour point	°C	DIN ISO 3016	-42
Total base number	mg/KOH	ASTM D 2896	11.3

The above values may vary within the commercial limits.



Made in Germany